RemoteSAT LAND Solutions RST100B SEA Solutions REDIAL Satellite Terminal BEAM **FIST 100** ··: iridium

RemoteSAT RST100B



The Beam RST100B is a single-channel intelligent voice and data communication terminal. For use inside a building, motor home, boat, vessel or a fixed site location providing easy satellite communication, utilising the latest Iridium satellite transceiver, the 9522B.

Voice communications are accessible via the intelligent POTS/RJ11 (Plain Old Telephone System) port for using up to 3 standard cordless or corded telephone handsets or for integrating with a PABX system enabling easy access from any handset connected to the PABX.

The optional compact Intelligent Handset with hang up cradle, SMS and phone book features can be used for voice calls. This handset is commonly used in conjunction with standard phone equipment.

The RST100B has an intelligent processor on board for managing an advanced RJ11 port, supporting abbreviated dialing, auto-dial, speed dial, call barring, call logging as well as configurable dial, ring and busy tones that can be set to country specific tones.

Internet, Fax and all the Iridium Data services are supported via the data port on the RST100B RemoteSAT terminal.

KEY FEATURES

- High quality robust design
- POTS/RJ11 Connectivity
- 9522B Iridium Satellite Transceiver
- Supports Intelligent Compact handset
- Supports Standard Phones
- Connect to PABX
- Phone Number Processing
- Voice, SMS, SBD and Circuit Switched Data capable
- Intelligent Processor & Interface
- External Ringer/Alert
- 11-32V DC power input
- AC Plug pack included 110/240 input
- Basic SMS support via laptop and RST100B management system
- Various marine, vehicular or fixed site antenna options available
- 12 month repair or replacement warranty















pots/rj11

pabx intelligent integration handset

siı

serial

Technical Specifications

POWER SPECIFICATIONS		
Power input voltage	11 - 32 V DC	
Power Consumption (AMPS)	12 V DC	24 V DC
Standby	0.350A	0.165A
Talk/Transmit	0.515A	0.255A
Standby - inc handset	0.47A	0.22A
Transmit - inc handset	0.59A	0.29A

ENVIRONMENT SPECIFICATIONS		
Temperature	Degrees °C	Degrees °F
Operating Range	-15 to +55	+5 to +131
Storage	-30 to +70	-22 to +158
Humidity	93% non condensing	
Vibration	2 Hz-13.2 Hz & 13.2 Hx-100 hz	
Corrosion	40 °C with 90% - 95% relative humidity after 2h salt spray	

CONNECTORS/INTERFACES	
Intelligent Handset	RJ45 DPL BUS
Telephone/POTS	RJ-11 2 -wire/TN12 or 600 ohm
Data Port	RS232 Serial Interface
Log Port	RS232 Serial Interface
Power	2 Pin screw type
LEDs	Power, Voicemail, SMS, Call & Signal

PHYSICAL SPECIFICATIONS		
Dimensions	mm	inches
Unit	225 x 277 x 53	8.9 x 10.9 x 2.1
Box	400 x 325 x 90	15.7 x 12.8 x 3.5
Weight	kgs	lbs
Unit	2.25	4.9
Вох	3.25	7.1

BOX	3.25	7.1
	CERTIFICATIONS	
EMC Compliance		
American bureau of Sh	nipping	
Germanischer Lloyd		
EC60945		
ridium		
CE Compliance		
Electrical Safety		

,	
C-Tick	
KIT CC	NTENTS
RST100B Terminal	
Mounting Brackets	
Data Cable	
110-240V AC Plug Pack	
DC 1.5m Power Cable	
CD - Beam Management Syst	em, AT Commands, Manuals
User & Installation Manual	

Accessories

RST970	Intelligent Iridium handset
RST740	Iridium Active Antenna
RST710	Mast/Pole Antenna
RST714	Whip Antenna
CVTIRI	Iridium Covert Antenna
RST932	Iridium Antenna Cable Kit Passive - 6m/19.7ft
RST933	Iridium Antenna Cable Kit Passive 12m/39.4ft

	1000	
	2	Traffic series
		Thorn
Cantain a	nd Crew Calling	



RST935	Iridium Antenna Cable Kit Passive 20m/65.6ft
RST936	Iridium Antenna Cable Kit Passive 30m/98ft
RST944	Iridium Active Cable Kit 23m/75.5ft
RST945	Iridium Active Cable Kit 34m/111.5ft
RST946	Iridium Active Cable Kit 52m/170.6ft
RST947	Iridium Active Cable Kit 75m/246.1ft
RST948	Iridium Active Cable Kit 104m/341.21ft







Global Head Office (Australia)

Beam Communications Pty Ltd 5/8 Anzed Court, Mulgrave, Victoria AUSTRALIA 3170

Tel: +61 3 8588 4500 Fax: +61 3 9560 9055

Website:www.beamcommunications.comGeneral:info@beamcommunications.comSupport:support@beamcommunications.comSales:sales@beamcommunications.com

Europe

Tel: +44 208 144 1405 Fax: +44 208 289 3542

United States

Tel: +1 800 250 5819 (USA toll free)

Fax: +1 888 972 8037

APPROVED BEAM RESELLER

T100B_REV01_

© 2016 Beam Communications Pty Ltd

AFRICA ASIA AUSTRALIA EUROPE MIDDLE EAST NORTH AMERICA SOUTH AMERICA