

VR7 0.96m Autopoint Technical Specifications



Mechanical

Reflector Type	0.96 meter
Mount Geometry	Elevation over Azimuth
Polarization	Vertical or Horizontal: 270° on both polarities
Deployment Sensors	GPS, Inclinometer
Azimuth	380°
Elevation	135° Physical Motion from Stow
Polarization (Skew)	Both polarities can be skewed by 270°
Deploy Elevation	1.5°/sec
Deploy Azimuth	4.0°/sec
Peaking Speed	0.25° increments

Warranty

1 year warranty, extended warranty available

- Intuitive touch screen controller supports auto or manual control
- Advanced self leveling feature aids in satellite acquisition
- 1 year standard warranty
- Advanced peaking algorithm on cross-polarization alignment
- No software to install
- Unaffected by magnetic compass distortion
- Compatible with most satellite modems
- Handheld, 2U or 4U controller
- Available in custom colors and configurations

Environmental

Deployed Wind Resistance	68mph (100kph)
Stowed Wind Resistance	In excess of 87mph (140kph)
Operational Temperature	-40°C to 65°C / -40°F to 150°F

Electrical

Transmit & Receive Cables	2 RG6 cables (35ft)
Control Cable	Interface cable (35ft) *Longer cables available
Transmit Power	1 to 200 Watt
Frequency	Ku Band

Physical

Length Stowed	68" (1.7m)
Width Stowed	39" (0.99m) w/reflector 19.5" (0.5m) w/o reflector
Height Stowed	12.5" (0.3m)
Weight	100lbs (45kg) w/o reflector and RF equip.

Solid State Controller

Standard Controller	Visual displays of azimuth, elevation, cross pole and signal strength. Controller has momentary buttons for all axis control movements.
Dimensions	7.5"l x 6.38"w x 1.75"h (190mm x 162mm x 44mm) *Custom rack mounts available
Interface	Serial or Ethernet
Electrical	100-240 VAC / 36 VDC

*Optional 2U or 4U Controller available

